

## SECURITHERM shower panel

Ref. 792400

Electronic battery-operated thermostatic







### DESCRIPTION

**SECURITHERM shower panel - Ref. 792400**

Thermostatic electronic shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With top inlet, via in-line stopcocks M $\frac{1}{2}$ ".  
SECURITHERM thermostatic mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Battery-operated with 223 6V Lithium battery.  
Infrared presence detection. Shower starts when hand is 4cm from the sensor.  
Shuts off on demand or automatically after ~60 seconds.  
Duty flush (~60 seconds every 24 hours after the last use).  
Flow rate set at 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
Concealed fixings.  
Filters and non-return valves.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792400**

Supply	6V battery
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS   
Warranty	

### ADVANTAGES



Total hygiene: operate without manual contact



Automatic anti-bacterial duty flush



Thermostatic temperature regulation



Instant shut-off if cold water fails

