

# SECURITHERM shower panel

Ref. 792400

Electronic battery-operated thermostatic



## DESCRIPTION

**SECURITHERM shower panel - Ref. 792400**





Thermostatic electronic shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 With top inlet, via in-line stopcocks M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Battery-operated with 223 6V Lithium battery.  
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.  
 Shuts off on demand or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Flow rate set at 6 lpm at 3 bar, can be adjusted.  
 Chrome-plated, tamperproof ROUND shower head.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792400**

Supply	6V battery
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	
Warranty	

## ADVANTAGES

-  Total hygiene: operate without manual contact
-  Automatic anti-bacterial duty flush
-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails

