## **TEMPOMATIC 4 electronic tap**

Ref. 443426

Integrated batteries



## **DESCRIPTION**

TEMPOMATIC 4 electronic tap - Ref. 443426

Electronic basin tap for panels:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises presence detection.

Chrome-plated stainless steel body L. 130mm.

Cap fixed in place by 2 concealed screws.

Installation for panels from 1 - 24mm.

Anti-blocking security.

Stopcock.

Suitable for people with reduced mobility.

30-year warranty.

## **TECHNICAL CHARACTERISTICS**

TEMPOMATIC 4 electronic tap - Ref. 443426

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	130mm
Flow rate	3 lpm
Norms	ACS 🧶 👺 SVGW
Warranty	30 g

## **ADVANTAGES**



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing tan

