

Mechanical basin mixer

Ref. 2446

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever










DESCRIPTION

Mechanical basin mixer - Ref. 2446





Wall-mounted mechanical basin mixer.
 Flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.
 Securitouch thermal insulation prevents burns.
 Body and spout with smooth interiors and low water volume (reduces bacterial development).
 Ø 40mm ceramic cartridge with pre-set maximum temperature limiter .
 Body and spout with smooth interiors and low water volume (reduces bacterial development). Flow rate regulated at 5 lpm.
 Chrome-plated brass body.
 Sculptured control lever.
 Supplied with STOP/CHECK connectors M1/2" M3/4" ideal for hospitals.
 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2446

Connector	M1/2"
Technology	Securitouch
Spout length	150mm
Flow rate	5 lpm
Finish	Chrome-plated brass
Norms	ACS     
Warranty	
Repairability	

ADVANTAGES

-  Smooth body/spout interior, reduces bacteria
-  Pre-set maximum temperature limiter
-  Securitouch thermal insulation prevents burns
-  Ergonomic, sculptured control lever

