

## Angled grab bar 90°, Ø 32mm

Ref. 5180S

UltraSatin polished satin stainless steel



### DESCRIPTION

Angled grab bar 90°, Ø 32mm - Ref. 5180S

Angled grab bar 90° for people with reduced mobility.  
 For use as a handrail (horizontal part) or as a grab bar (vertical part) for WCs or baths.  
 Universal for either left or right side.  
 Dimensions: 300 x 300mm, Ø 32mm.  
 Bacteriostatic 304 stainless steel tube.  
 UltraSatin polished satin stainless steel, uniform non-porous surface for easy maintenance and hygiene.  
 Plate welded to the tube by invisible safety bead weld (process exclusive to "ArN-Securit").  
 40mm gap between the bar and the wall: minimal space prevents the forearm passing between the bar and the wall, reducing the risk of fracture in case of loss of balance.  
 Concealed fixings, secured to wall by a 3-hole, 304 stainless steel plate, Ø 72mm.  
 Fixing plates and cover plates in 304 stainless steel.  
 Supplied with stainless steel screws for concrete walls.  
 Tested to over 200kg. Maximum recommended user weight: 135kg.  
 30-year warranty. CE marked.

### TECHNICAL CHARACTERISTICS

Angled grab bar 90°, Ø 32mm - Ref. 5180S

Height	300mm
Length	300mm
Diameter	Ø 32mm
Width to the wall	40mm
Finish	304 stainless steel UltraSatin polished satin
Norms	
Warranty	

### ADVANTAGES



304 stainless steel: reduces bacterial development



Tested to over 200kg



40mm gap between bar and wall: minimal space



UltraSatinbasin: Smooth surface easy to clean

