

## Mechanical mixer for sinks or troughs

Ref. 2210

Single hole mechanical mixer with swivelling spout H. 145mm L. 215mm





### DESCRIPTION

Mechanical mixer for sinks or troughs - Ref. 2210

Deck-mounted mechanical sink mixer.  
 Single hole mechanical mixer with swivelling spout H. 145mm L. 225mm fitted with hygienic flow straightener.  
 Spout suitable for fitting a BIOFIL point-of-use filter.  
 Ø 40mm ceramic cartridge with pre-set maximum temperature limiter.  
 Body and spout with smooth interiors.  
 Body and spout made from chrome-plated brass.  
 Flow rate limited to 9 lpm at 3 bar.  
 Sculptured control lever.  
 PEX flexibles F3/8".  
 Fixing reinforced by 2 stainless steel rods.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Single hole mixer suitable for people with reduced mobility.  
 30-year warranty.





### TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2210

|                     |  |
|---------------------|--|
| Connector           | F3/8"  |
| Drop height         | 145mm  |
| Spout length        | 215mm  |
| Flow rate           | 9 lpm at 3 bar   |
| Temperature limiter | Yes  |
| Finish              | Chrome-plated brass  |
| Norms               | ACS NF   |
| Warranty            |   |
| Repairability       |   |



### ADVANTAGES

-  Hygiene: smooth interior reduces bacteria
-  Pre-set maximum temperature limiter
-  Ergonomic sculptured control lever is easy to grip
-  Comfort: Optimum drop height and spout projection

