

## TEMPOMATIC PRO electronic tap

Ref. 445253

Mains supply



### DESCRIPTION

TEMPOMATIC PRO electronic tap - Ref. 445253

Deck-mounted electronic basin tap:  
 Independent IP65 electronic control unit.  
 230/12V mains supply with transformer.  
 Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Shock-resistant infrared presence detection sensor.  
 Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.  
 PEX flexible with filter and solenoid valve M3/8".  
 360° swivelling spout with smooth interior (reduces bacterial development).  
 Removable spout for cleaning.  
 Anti-blocking security.  
 Two shut-off options:  
 Standard mode: timed flow with automatic shut-off.  
 ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.  
 Thermal shocks are possible.  
 Suitable for people with reduced mobility.  
 30-year warranty.





### TECHNICAL CHARACTERISTICS

TEMPOMATIC PRO electronic tap - Ref. 445253

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Norms	ACS  CE
Warranty	



### ADVANTAGES

-  Exceptional water savings: 85%
-  Hygiene: no manual contact
-  Multiple modes of operation
-  Anti-bacterial proliferation duty flush

