

TEMPOMATIC PRO electronic tap

Ref. 445253

Mains supply




DESCRIPTION

TEMPOMATIC PRO electronic tap - Ref. 445253

Deck-mounted electronic basin tap:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Shock-resistant infrared presence detection sensor.
 Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.
 PEX flexible with filter and solenoid valve M3/8".
 360° swivelling spout with smooth interior (reduces bacterial development).
 Removable spout for cleaning.
 Anti-blocking security.
 Two shut-off options:
 Standard mode: timed flow with automatic shut-off.
 ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.
 Thermal shocks are possible.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

TEMPOMATIC PRO electronic tap - Ref. 445253

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Norms	ACS  
Warranty	



ADVANTAGES

-  Exceptional water savings: 85%
-  Hygiene: no manual contact
-  Multiple modes of operation
-  Anti-bacterial proliferation duty flush

