## TEMPOMATIC PRO electronic tap

Ref. 445257

**Battery-operated** 



## **DESCRIPTION**

**TEMPOMATIC PRO electronic tap - Ref. 445257** 

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

123 6V Lithium battery-operated.

Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods. PEX flexible with filter and solenoid valve M3/8".

360° swivelling spout with smooth interior (limits bacterial niches).

Removable spout for cleaning.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

## **TECHNICAL CHARACTERISTICS**

TEMPOMATIC PRO electronic tap - Ref. 445257

| Supply       | 6V battery      |
|--------------|-----------------|
| Connector    | M3/8"           |
| Technology   | Electronic      |
| Drop height  | 310mm           |
| Spout length | 200mm           |
| Flow rate    | 4 lpm           |
| Norms        | ACS () (E       |
| Warranty     | 30g<br>WARRANTY |

## **ADVANTAGES**



Exceptional water savings: 85%




Hygiene: no manual contact



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush



© DELABIE https://www.delabie.com