

SECURITHERM EP pressure-balancing basin mixer

Ref. 2521LEP

Single hole mechanical mixer H. 85mm, L. 135mm



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521LEP

Deck-mounted mechanical basin mixer with pressure-balancing basin mixer. Single hole mixer with spout H. 85mm L. 135mm fitted with BIOSAFE hygienic spout outlet.

Ø 40mm ceramic cartridge with pressure-balancing with pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if cold water supply fails (and vice versa).

Flow rate limited to 5 lpm at 3 bar.

Hygiene control lever L. 150mm.

Without pop-up waste.

F3/8" PEX flexibles with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.







Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521LEP

Connector	F3/8"
Technology	SECURITHERM EP mechanical mixer
Height	185mm
Drop height	85mm
Spout length	135mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS    
Warranty	
Repairability	

ADVANTAGES



HW flow rate reduced if CW fails



EP: reduces temperature variations



Hygiene: BIOSAFE hygienic outlet with no grid



Hygiene control lever requires no manual contact

