

## Mechanical basin mixer

Ref. 2446S

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever








### DESCRIPTION

Mechanical basin mixer - Ref. 2446S

Wall-mounted mechanical basin mixer.  
Swivelling, flat under-spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.  
Securitouch thermal insulation prevents burns.  
Ø 40mm ceramic cartridge and pre-set maximum temperature limiter.  
Body and spout with smooth interiors and low water volume (reduce niches where bacteria can develop).  
Flow rate regulated at 5 lpm.  
Chrome-plated brass body.  
Sculptured control lever.  
Supplied with standard connectors, M1/2" M3/4".  
30-year warranty.

### TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2446S

Connector	M1/2"
Technology	Securitouch
Spout length	150mm
Flow rate	5 lpm
Finish	Chrome-plated brass
Norms	ACS   
Warranty	
Repairability	

### ADVANTAGES



Smooth body/spout interior, reduces bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Ergonomic, sculptured control lever

