

# Mechanical sink mixer

Ref. 2519L

Wall-mounted mixer with swivelling spout L. 200, Hygiene lever L. 150







## DESCRIPTION

**Mechanical sink mixer - Ref. 2519L**





Wall-mounted mechanical sink mixer.  
 Wall-mounted mixer with swivelling, tubular spout L. 200mm with smooth interior (reduces bacterial development).  
 Auto-draining under-spout Ø 22mm with star-shaped, brass flow straightener.  
 Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.  
 Flow rate 26 lpm at 3 bar.  
 Hygiene control lever L. 150mm.  
 Mixer with 150mm centres supplied with offset STOP/CHECK wall connectors, M1/2" M3/4", suitable for hospitals.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Mechanical sink mixer - Ref. 2519L**

|               |   |
|---------------|---|
| Connector     | M1/2"   |
| Spout length  | 200mm   |
| Flow rate     | 26 lpm  |
| Finish        | Chrome-plated brass   |
| Norms         | ACS   |
| Warranty      |    |
| Repairability |    |

## ADVANTAGES

-  Hygiene: spout with smooth interior
-  Pre-set maximum temperature limiter
-  Hygiene control lever requires no manual contact
-  Auto-draining spout reduces bacterial development

