

SECURITHERM Securitouch thermostatic shower-bath mixer

Ref. H9752S

Dual control thermostatic shower mixer



DESCRIPTION

SECURITHERM Securitouch thermostatic shower-bath mixer - Ref. H9752S

SECURITHERM dual control thermostatic shower-bath mixer. Mixer with anti-scalding safety: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

¼-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 41°C.

Double temperature limiter: first limiter set at 38°C (can be overridden), second limiter set at 41°C.

Straight forward thermal shock procedure without removing the control knob or shutting off the cold water supply

Thermostatic mixer fitted with an automatic diverter with low pressure lock maintains the shower position even if the flow rate is too low.

Chrome-plated brass body and ERGO control knobs.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.






Mixer with M1/2" M3/4" offset standard wall connectors.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Shower mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower-bath mixer - Ref. H9752S

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer
Width	286mm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	

ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Double maximum temperature limiter



Securitouch anti-scalding thermal insulation



Thermostatic: total temperature stability

