

# Sequential thermostatic shower mixer

Ref. H9640S

Thermostatic mixer with no non-return valves, top outlet






## DESCRIPTION

**Sequential thermostatic shower mixer - Ref. H9640S**





SECURITHERM thermostatic sequential shower mixer.  
 Thermostatic sequential mixer: opens and closes with cold water.  
 Mixer with no non-return valves on the inlets (reduces bacterial proliferation).  
 No risk of cross flow between hot and cold water.  
 Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.  
 Prevents cold showers: shuts off automatically if hot water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Scale-resistant thermostatic sequential cartridge for adjusting the flow rate and the temperature.  
 Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.  
 Thermal shocks are possible.  
 Body with smooth interior and low water volume (reduces niches where bacteria can develop).  
 Flow rate regulated at 9 lpm.  
 Chrome-plated brass body and Hygiene control lever L. 100mm.  
 3/4" top shower outlet.  
 Wall-mounted mixer with offset standard connectors, M1/2" M3/4".  
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics  
 Sequential mixer suitable for people with reduced mobility.  
 Shower mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Sequential thermostatic shower mixer - Ref. H9640S**

Technology	SECURITHERM Securitouch sequential thermostatic mixer
Width	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS  
Warranty	

## ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: complete temperature stability

