

Twin hole pillar-mounted mixer - 100 lpm

Ref. 5603

On pillar mounts

DESCRIPTION

Twin hole pillar-mounted mixer - 100 lpm - Ref. 5603

Twin hole mixer, M3/4" with 150mm centres on pillar mounts for plunge sinks. Swivelling, tubular spout Ø 22mm H. 380mm L. 300mm.

Star-shaped, brass flow straightener.

Water-free, guided valve heads with reinforced mechanisms.

Shock-resistant ergonomic ball levers.

Flow rate 100 lpm at 3 bar suitable for plunge sinks.

Full flow rate within the first 90°.

Spout with smooth interior.




One-piece body and spout in chrome-plated brass.

Reinforced fixings and recessed inlets.

30-year warranty.

TECHNICAL CHARACTERISTICS

Twin hole pillar-mounted mixer - 100 lpm - Ref. 5603

Connector	M3/4"
Height	445mm
Drop height	380mm
Spout length	300mm
Flow rate	100 lpm
Finish	Chrome-plated brass
Norms	ACS 
Warranty	
Repairability	



ADVANTAGES



Flow rate 100 lpm at 3 bar



Shock-resistant control levers for intensive use



One-piece body and brass spout for commercial use



Spout with smooth interior

