TEMPOMATIC MIX 4 electronic mixer

Ref. 490106LH

Integrated batteries



TEMPOMATIC MIX 4 electronic mixer - Ref. 490106LH

Deck-mounted electronic basin mixer:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Sensor at the end of the spout optimises presence detection.

Chrome-plated stainless steel body.

Cap fixed in place by 2 concealed screws.

PEX flexibles with filters and non-return valves .

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Side temperature control with long lever and adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490106LH

| Supply | 6V batteries |
|---------------|------------------|
| Connector | F3/8" |
| Technology | Electronic |
| Drop height | 70mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Norms | ACS 🔘 🦫 SVGW |
| Warranty | 30 g |
| Repairability | 50° SEPARABILITY |



ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Batteries integrated into the body of the mixer



Integrated solenoid valve



© DELABIE https://www.delabie.com