

TEMPOMATIC MIX 4 electronic mixer

Ref. 490000

Recessed mains supply, stopcocks






DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000

Deck-mounted electronic basin mixer:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Presence detection sensor at the end of the spout optimises detection.
Chrome-plated stainless steel body.
Cap fixed in place by 2 concealed screws.
PEX flexibles with stopcocks F3/8" with stopcocks and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000

| | |
|---------------|---|
| Supply | 230/6V mains supply (recessed) |
| Connector | F3/8" |
| Technology | Electronic |
| Drop height | 70mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Norms |    |
| Warranty |  |
| Repairability |  |



ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Recessed mains supply



Anti-bacterial proliferation duty flush

