

## TEMPOMATIC MIX 4 electronic mixer

Ref. 490000LH

Recessed mains supply, stopcocks








### DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000LH

Deck-mounted electronic basin mixer:  
230/6V recessed mains supply.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Presence detection sensor at the end of the spout optimises detection.  
Chrome-plated stainless steel body.  
Cap fixed in place by 2 concealed screws.  
PEX flexibles F3/8" with filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000LH

|               |   |
|---------------|---|
| Supply        | 230/6V mains supply (recessed)  |
| Connector     | F3/8"   |
| Technology    | Electronic  |
| Drop height   | 70mm  |
| Spout length  | 105mm   |
| Flow rate     | 3 lpm   |
| Norms         |    |
| Warranty      |    |
| Repairability |    |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Recessed mains supply



Integrated solenoid valve

