

## BINOPTIC electronic tap

Ref. 478015

Battery-operated








### DESCRIPTION

#### BINOPTIC electronic tap - Ref. 478015





Deck-mounted electronic basin tap:  
 Independent IP65 electronic control unit.  
 123 6V Lithium battery-operated.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated brass body.  
 PEX flexible with filter and solenoid valve M3/8".  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

#### BINOPTIC electronic tap - Ref. 478015

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Norms	ACS   
Warranty	
Repairability	

### ADVANTAGES

-  80% water savings
-  Hygiene: no manual contact
-  6V batteries
-  Anti-bacterial proliferation duty flush

