

TEMPOMATIC MIX 2 electronic mixer

Ref. 494000

Electronic mains supply



DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 494000

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated brass body.
PEX flexibles with filters and solenoid valves M3/8".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter.
Solenoid valves are upstream of the mixing chamber.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref. 494000

| | |
|--------------|----------------------|
| Supply | 230/12V mains supply |
| Connector | M3/8" |
| Technology | Electronic |
| Drop height | 125mm |
| Spout length | 145mm |
| Flow rate | 4 lpm |
| Norms | ACS CE NF |
| Warranty | 30 YEAR WARRANTY |

ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



LED diagnostic aid



Independent IP65 electronic unit

