

TEMPOMATIC Electronic tap

Ref. 441157

Mains supply



DESCRIPTION

TEMPOMATIC Electronic tap - Ref. 441157

Cross wall electronic basin tap:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Chrome-plated fixed spout L. 170mm with anti-rotating pin and back-nut.
 Plate is flush to wall.
 Shockproof infrared presence detection sensor for wall ≤ 155mm
 Anti-blocking security.
 For walls ≤ 155mm.
 Solenoid valve with integrated filter.
 Threaded rods can be cut-to-size.
 Suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC Electronic tap - Ref. 441157

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Depth	165mm
Spout length	170mm
Flow rate	3 lpm
Norms	ACS CE
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

