

TEMPOMIX time flow mixer

Ref. 795000

With stopcocks











DESCRIPTION

TEMPOMIX time flow mixer - Ref. 795000

Deck-mounted single control time flow basin mixer:
 Soft-touch operation.
 Temperature control and operation via the push-button.
 Time flow ~7 seconds.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Chrome-plated brass body.
 Ergonomic chrome-plated metal push-button.
 PEX flexibles with stopcocks F3/8", filters and non-return valves.
 Fixing reinforced by 2 stainless steel rods.
 Adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795000

| | |
|---------------|---|
| Connector | F3/8" |
| Technology | Time flow |
| Drop height | 60mm |
| Spout length | 110mm |
| Flow rate | 3 lpm |
| Norms |       |
| Warranty |  |
| Repairability |  |

ADVANTAGES



Exceptional water savings: 85%



Chrome-plated solid brass, reinforced fixings



Soft-touch operation

