

## TEMPOSOFT MIX 2 time flow mixer

Ref. 742500LH

Soft-touch operation, stopcocks







### DESCRIPTION

TEMPOSOFT MIX 2 time flow mixer - Ref. 742500LH





Deck-mounted time flow basin mixer:  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Tamperproof scale-resistant flow straightener.  
 Chrome-plated brass body.  
 PEX flexibles F3/8" with stopcocks, filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Side temperature control with long lever and adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOSOFT MIX 2 time flow mixer - Ref. 742500LH

Connector	F3/8"
Technology	Time flow
Drop height	85mm
Spout length	100mm
Flow rate	3 lpm
Norms	ACS  
Warranty	
Repairability	

### ADVANTAGES

-  Exceptional water savings: 85%
-  Reinforced fixings
-  Temperature selection
-  Sleek lines

