

SECURITHERM shower panel

Ref. 792310

Thermostatic time flow






DESCRIPTION

SECURITHERM shower panel - Ref. 792310

Thermostatic time flow shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Concealed inlet via flexibles M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Soft-touch operation.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
 Time flow shower valve ~30 seconds.
 Flow rate set at 6 lpm at 3 bar.
 Concealed fixings.
 Filters and non-return valves.
 Time flow shower panel suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792310

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	   
Warranty	



ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

