

# SECURITHERM shower panel

Ref. 792390

Thermostatic mechanical dual control

## DESCRIPTION

**SECURITHERM shower panel - Ref. 792390**

Dual control thermostatic shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.  
Handset with removable flexible via push-fit rapid STOP connector.  
2 non-time flow 1/4-turn valves to control fixed shower head and handset on flexible hose (wall support supplied).  
Concealed fixings.  
Filters and non-return valves.  
Shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792390**

|                     |                                                                                                                                                                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector           | M1/2"                                                                                                                                                                                                                                                           |
| Technology          | Non-time flow                                                                                                                                                                                                                                                   |
| Height              | 1050mm                                                                                                                                                                                                                                                          |
| Depth               | 65mm                                                                                                                                                                                                                                                            |
| Width               | 210mm                                                                                                                                                                                                                                                           |
| Flow rate           | 6 lpm                                                                                                                                                                                                                                                           |
| Temperature limiter | Thermostatic                                                                                                                                                                                                                                                    |
| Finish              | Aluminium                                                                                                                                                                                                                                                       |
| Norms               | ACS    |
| Warranty            |                                                                                                                                                                              |



## ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Aluminium panel, brass controls

