

TEMPOMIX time flow shower kit

Ref. 790909

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790909

Time flow shower kit with recessed waterproof housing:
 Chrome-plated wall plate Ø 195mm.
 Standard recessed housing.
 Recessing depth can be adjusted from 28 to 43mm.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 M1/2" connectors for copper tubes Ø 14mm.
 Integrated non-return valves and filters.
 Chrome-plated metal push-button.
 Suitable for people with reduced mobility.
 30-year warranty.
 Integrated non-return valves and filters. This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES



80% water savings



Wall recessed installation





Time flow system tested to over 500,000 operations



Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790909

Connector	1/2"
Technology	Time flow
Flow rate	6 lpm
Norms	ACS  
Warranty	