

TEMPOMIX time flow shower kit

Ref. 790709

Single control time flow






DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790709

Recessed time flow shower kit:
 Stainless steel wall plate 160 x 160mm.
 Standard recessing housing.
 Recessing depth can be adjusted from 28 to 48mm.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 M1/2" connections for copper tubes Ø 14mm.
 Integrated non-return valves and filters.
 Chrome-plated metal control.
 30-year warranty.
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790709

Connector	1/2"
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	6 lpm
Norms	ACS  
Warranty	

ADVANTAGES



80% water savings



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

