

## TEMPOMIX time flow shower mixer

Ref. 790427

Single control time flow









### DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790427

Recessed time flow shower kit:  
 Stainless steel wall plate 160 x 160mm.  
 Standard recessing housing.  
 Recessing depth can be adjusted from 28 to 48mm.  
 TEMPOMIX 3/4" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds.  
 Flow rate 12 lpm at 3 bar.  
 M1/2" connections for Ø 14mm copper tubes.  
 Integrated non-return valves and filters.  
 Chrome-plated metal push-button.  
 Integrated non-return valves and filters.  
 30-year warranty.  
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

### TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790427

|            |   |
|------------|---|
| Connector  | 1/2"  |
| Technology | Time flow   |
| Height     | 160mm   |
| Width      | 160mm   |
| Flow rate  | 12 lpm  |
| Norms      |      |
| Warranty   |    |

### ADVANTAGES



Wall recessed installation



System tested to over 500000 operations



Soft-touch operation

