

## TEMPOSOFT 2 time flow shower kit

Ref. 749429

Time flow



### DESCRIPTION

TEMPOSOFT 2 time flow shower kit - Ref. 749429

Recessed time flow shower kit:  
TEMPOSOFT 2 M $\frac{1}{2}$ " time flow valve for mixed water supply.  
For recessed installation.

Bright polished stainless steel 304 wall plate Ø 130mm.

Recessing depth can be adjusted from 1 to 5mm.

Soft-touch operation.

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof ROUND shower head with scale-resistant nozzle and automatic flow rate regulation.

Body and shower head in chrome-plated solid brass.



Suitable for people with reduced mobility.

30-year warranty.

This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

### TECHNICAL CHARACTERISTICS

TEMPOSOFT 2 time flow shower kit - Ref. 749429

Connector	$\frac{1}{2}$ "
Technology	Time flow
Flow rate	6 lpm
Norms	ACS 
Warranty	

### ADVANTAGES



80% water savings



Soft-touch operation



System tested to over 500,000 operations

