

TEMPOFLUX 2 direct flush valve

Ref. 762902

Time flow direct flush WC valve



DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762902

Flush system without cistern: directly connected to pipework.
 Chrome-plated metal wall plate Ø 195mm.
 Concealed mechanical fixing of the wall plate.
 Multipurpose recessing housing.
 Recessing depth can be adjusted from 0 - 20mm.
 3L/6L dual flush, can be adjusted to 2L/4L.
 Soft-touch operation.
 Vacuum breaker.
 Integrated stopcock and flow rate / flush volume adjuster.
 Solid brass body.
 Chrome-plated metal push-button.
 In-line inlet M $\frac{3}{4}$ ".
 Outlet connection for PVC tube Ø 26/32mm.
 Acoustic level complies with European standard EN 12541 class II.
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
 Base flow rate: 1L/sec at 1 bar dynamic pressure.
 Compatible with rain water.
 Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
 30-year warranty.
 This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

ADVANTAGES



Soft-touch operation



Dual flush 3L/6L






No cistern: no stagnant water



Recessed installation

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762902

| | |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector | 3/4" |
| Technology | Time flow |
| Flow rate | 3L/6L |
| Finish | Chrome-plated metal |
| Norms |   |
| Warranty |  |

