

# TEMPOFLUX 2 direct flush valve

Ref. 762150

Direct flush WC valve






## DESCRIPTION

**TEMPOFLUX 2 direct flush valve - Ref. 762150**



Flush system without cistern: directly connected to pipework.  
 For walls ≤ 140mm.  
 3L/6L dual flush can be adjusted to 2L/4L.  
 Soft-touch operation.  
 Vacuum breaker.  
 Integrated stopcock and flow rate / flush volume adjuster.  
 Solid brass body.  
 Chrome-plated metal push-button.  
 In-line inlet M $\frac{3}{4}$ ".  
 Outlet connection for PVC tube Ø 26/32mm.  
 Threaded rod can be cut to size.  
 Acoustic level complies with European standard EN 12541 class II.  
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for rimless WC pans without flow rate regulation.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## ADVANTAGES

-  Soft-touch operation
-  Dual flush 3L/6L
-  No cistern: no stagnant water
-  Cross wall installation

## TECHNICAL CHARACTERISTICS

**TEMPOFLUX 2 direct flush valve - Ref. 762150**

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	140mm
Flow rate	3L/6L
Norms	 
Warranty	