TEMPOFLUX 1 direct flush valve

Ref. 761627

Time flow direct flush WC valve



DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761627

Recessed time flow valve for direct flush: Stainless steel control plate 220 x 170mm.

Multipurpose recessing housing.

Soft-touch operation.

Time flow ~7 seconds.

Vacuum breaker.

Integrated stopcock and flow/volume rate adjuster.

Solid brass body and chrome-plated push-button.

In-line inlet M¾".

Outlet connection for PVC tube Ø 26/32mm.

Upstream supply pipes: minimum \emptyset 20mm required at all points (including connectors).

Base flow rate: 1 L/sec at 1 bar dynamic pressure.

Compatible with rain water.

Suitable for people with reduced mobility.

30-year warranty.

This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761627

Connector	3/4"
Height	220mm
Width	170mm
Norms	5
Warranty	30 g

ADVANTAGES



No cistern: no stagnant water



Wall recessed installation



Powerful flush and immediately available



Direct flush reduces the risk of leaks

