

TEMPOFLUX 1 direct flush kit

Ref. 761003

Time flow direct flush WC valve





DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761003

Flush system without cistern: directly connected to pipework.
 For wall-mounted exposed installation.
 Soft-touch operation.
 Time flow ~7 seconds.
 Vacuum breaker.
 Integrated stopcock and flow rate / flush volume rate adjuster.
 Chrome-plated solid brass body and push-button.
 Angled inlet M $\frac{3}{4}$ ".
 Upstream supply pipes: minimum \varnothing 20mm required at all points (including connectors).
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.
 With stainless steel flush tube, collar and connection washer.
 Compatible with rain water.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761003

| | |
|-----------|---|
| Connector | $\frac{3}{4}$ " |
| Height | 565mm |
| Length | 215mm |
| Norms |   |
| Warranty |  |

ADVANTAGES



No cistern: no stagnant water



Chrome-plated solid brass



Powerful flush and immediately available



Direct flush reduces the risk of leaks

