

## TEMPOFLUX 1 direct flush kit

Ref. 761025

Time flow direct flush WC system



### DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761025

Flush system without cistern: directly connected to pipework.  
 For wall-mounted exposed installation.  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Vacuum breaker.  
 Chrome-plated solid brass body and push-button.  
 Angled inlet M $\frac{3}{4}$ ".  
 With flush tube  $\varnothing$  25mm and  $\varnothing$  24mm (replacements for SCHELL & BINE 120000 models).  
 Upstream supply pipes: minimum  $\varnothing$  20mm required at all points (including connectors).  
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.





### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761025

Connector	$\frac{3}{4}$ "
Norms	
Warranty	



### ADVANTAGES

-  No cistern: no stagnant water
-  Chrome-plated solid brass
-  Powerful flush and immediately available
-  Direct flush reduces the risk of leaks

