## Auto-rewind 304 stainless steel hose reel

Ref. 5675T2

With 15m flexible hose and hand spray



## **ADVANTAGES**



Easy to clean: smooth surfaces



Stainless steel hose reel with hose lock



304 stainless steel: reduces bacterial development

## **DESCRIPTION**

Auto-rewind 304 stainless steel hose reel - Ref. 5675T2

Auto-rewind hose reel with flexible hose L. 15m and guide rollers: Maximum temperature  $50^{\circ}$ C.

Flow rate 23 lpm at 3 bar.


Maximum pressure 20 bar, 12 bar with trigger-op hand spray. Hose reel with 304 Stainless steel base and drum Ø 390mm. Order separately: an angled stopcock with integrated vacuum breaker to

Order separately: an angled stopcock with integrated vacuum breaker to prevent the back flow of polluted water into the mains supply. Stainless steel hose reel with 30-year warranty.

## TECHNICAL CHARACTERISTICS

Auto-rewind 304 stainless steel hose reel - Ref. 5675T2

Connector	3/4"
Height	400mm
Depth	410mm
Length	186mm
Flow rate	14 lpm
Finish	304 Stainless steel
Warranty	30 gg WARRANTY
Repairability	50 g



© DELABIE https://www.delabie.com