

# TEMPOMATIC electronic shower kit

Ref. 452159

Electronic



## DESCRIPTION

**TEMPOMATIC electronic shower kit - Ref. 452159**

Cross wall electronic shower kit:  
 TEMPOMATIC electronic valve for mixed water supply.  
 For walls ≤ 155mm.  
 Power supply by electronic unit with solenoid valve 1/2".  
 230/12V transformer.  
 2 operation modes:  
 - Automatic activation via presence detection.  
 - Voluntary ON/OFF activation by passing the hand in front of sensor ~10 cm.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Adjustable time flow from 30 to 60 seconds.  
 Flow rate set at 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Chrome-plated solid brass.  
 Wall plate flush to the wall.  
 Threaded rods can be cut-to-size.  
 Electronic shower kit suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**TEMPOMATIC electronic shower kit - Ref. 452159**

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Norms	ACS CE
Warranty	

## ADVANTAGES



230/12V



Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes

