

# SECURITHERM time flow shower panel

Ref. 792313

Time flow thermostatic







## DESCRIPTION

**SECURITHERM time flow shower panel - Ref. 792313**

Thermostatic time flow shower panel:  
 Large model satin stainless steel shower panel for wall-mounted, exposed installation.  
 Concealed inlet via flexibles M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic shower mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar.  
 M $\frac{1}{2}$ " stopcocks.  
 Concealed fixings.  
 Filters and non-return valves.  
 Shower panel suitable for people with reduced mobility.  
 30-year warranty.

## ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

## TECHNICAL CHARACTERISTICS

**SECURITHERM time flow shower panel - Ref. 792313**

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  
Warranty	

