TEMPOMIX time flow shower mixer

Ref. 790925

Single control time flow

DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790925

Recessed time flow shower kit:
Chrome-plated Ø 195mm wall plate.
Standard recessing housing.
Recessing depth adjustable from 28 - 43mm.
TEMPOMIX ¾" single control mixer.
Ligature-resistant collar.
Temperature control and operation via the push-button.
Maximum temperature limiter (can be adjusted by the installer).
Time flow ~30 seconds, soft-touch operation.
Flow rate 12 lpm at 3 bar.
M½" connectors for Ø 15mm copper tubes.
Integrated non-return valves and filters.
Chrome-plated metal control.
30-year warranty.
As this model does not come with waterproof recessing housing the installer must ensure the watertightness of the recessing area and allow for run-off of leaks and condensation (see installation guide).

ADVANTAGES

- Recessed wall installation
- Time flow system tested to 500,000+ operations
- Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790925

Connector	M1/2'' Ø 15mm
Technology	Time flow
Flow rate	12 lpm
Norms	ACS CE
Warranty	30 YEAR WARRANTY