

## SECURITHERM shower panel

Ref. 792504

Electronic mains supply thermostatic





### DESCRIPTION

**SECURITHERM shower panel - Ref. 792504**





Electronic thermostatic shower panel:  
 Large stainless steel panel for wall-mounted, exposed installation.  
 Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Mains supply 230/6V.  
 Shower starts when electronic push-button is pressed.  
 Shuts off voluntarily or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Flow rate 6 lpm at 3 bar, can be adjusted, rain-effect spray.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Integrated soap dish.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 30-year warranty.


### TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792504**

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  

### ADVANTAGES

-  Exceptional water savings: 80%
-  Anti-bacterial proliferation duty flush
-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails



---

Warranty

