

# TEMPOMIX 3 time flow shower kit

Ref. 794450

Time flow single control




## DESCRIPTION

**TEMPOMIX 3 time flow shower kit - Ref. 794450**

Exposed time flow shower kit:  
 TEMPOMIX 3 single control mixer ¾", top outlet.  
 For wall-mounted, exposed installation.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant TONIC JET shower head with automatic flow rate regulation.  
 Chrome-plated solid brass.  
 Integrated filters and non-return valves.  
 Chrome-plated metal push-button.  
 Shower column Ø 16mm with reinforced collar (fixing plate and screws included).  
 M½" offset connectors for 130 - 170mm centres.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow shower kit - Ref. 794450**

Connector	M½"
Technology	Time flow
Height	1,010mm
Width	150mm
Flow rate	6 lpm
Norms	 ACS 
Warranty	



## ADVANTAGES



80% water savings



Soft-touch operation



Time flow system tested to over 500,000 operations

