


# TEMPOMIX 3 time flow shower mixer

Ref. 794400

Time flow single control






## DESCRIPTION

TEMPOMIX 3 time flow shower mixer - Ref. 794400

Exposed time flow shower mixer:  
 TEMPOMIX 3 single control mixer, top outlet M $\frac{3}{4}$ ".  
 For wall-mounted, exposed installation.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar, can be adjusted from 6 - 12 lpm.  
 Chrome-plated solid brass.  
 Integrated filters and non-return valves.  
 Chrome-plated metal push-button.  
 M $\frac{1}{2}$ " offset connectors for 130 - 170mm centres.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow shower mixer - Ref. 794400

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Width	150mm
Flow rate	9 lpm
Norms	ACS  
Warranty	

## ADVANTAGES



Soft-touch operation



Time flow system tested to over 500,000 operations

