

TEMPOMATIC MIX 4 electronic mixer

Ref. 49000015

Recessed mains supply, stopcocks Ø 15mm





DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000015

Deck-mounted electronic basin mixer:
230/6V recessed mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Presence detection sensor at the end of the spout optimises detection.
Chrome-plated stainless steel body.
Cap fixed in place by two concealed screws.
PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with standard lever and adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000015

| | |
|--------------|---|
| Supply | 230/6V mains supply (recessed) |
| Connector | M1/2" Ø 15mm |
| Technology | Electronic |
| Drop height | 70mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Norms |  |
| Warranty |  |

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Recessed mains supply



Integrated solenoid valve

