

TEMPOMATIC direct flush valve

Ref. 463547

Electronic mains supply - sea water compatible





DESCRIPTION

TEMPOMATIC direct flush valve - Ref. 463547





Recessed electronic direct flush valve:
 Mains supply with 1" solenoid valve.
 230/12V transformer.
 IP65 electronic housing unit.
 Housing recessed behind a satin finish stainless steel plate 220 x 170mm.
 Shock-resistant infrared presence detection sensor.
 Voluntary activation (when hand is detected ~10cm in front of the sensor) or automatic flush when the user leaves.
 Time flow ~7 seconds can be adjusted from 3 - 12 seconds.
 Detection distance, flow rate and flush volume can be adjusted.
 Sea water compatible.
 Base flow rate: 1 L/sec.
 Suitable for rimless WC pans.
 30-year warranty.
 This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMATIC direct flush valve - Ref. 463547

Supply	Mains supply 230/12V
Connector	1"
Technology	Electronic
Height	220mm
Width	170mm
Finish	Satin finish stainless steel
Norms	
Warranty	

ADVANTAGES

-  Total hygiene: no manual contact
-  Direct flush: no water stagnation
-  Voluntary or automatic flush
-  Recessed installation

