

SECURITHERM time flow shower panel

Ref. 79230415

Thermostatic time flow




DESCRIPTION

SECURITHERM time flow shower panel - Ref. 79230415

Thermostatic time flow shower panel:
 Large model satin stainless steel shower panel for wall mounted, exposed installation.
 Top inlet via in-line stopcocks and Ø 15mm conical inlets.
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 41°C.
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
 Thermal shocks are possible.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
 Integrated soap dish.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 79230415

| | |
|---------------------|-------------------------------------------------------------------------------------|
| Connector | M½" Ø 15mm |
| Technology | Time flow |
| Height | 1220mm |
| Depth | 100mm |
| Width | 250mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Stainless steel |
| Warranty |  |

ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



80% water savings



Stainless steel panel, brass controls

