

KOMPACT washbasin and floor-standing WC combination

Ref. 160600

Polished satin 304 stainless steel, Wall mount, Floor mount WC on RHS

DESCRIPTION

KOMPACT washbasin and floor-standing WC combination - Ref. 160600

Combination unit: washbasin and floor-standing WC pan on right side with recessed toilet roll holder.

Wall-mounted installation with 3 access panels, 2 on the sides and 1 on the top with theft prevention TORX security screws.

Bacteriostatic 304 stainless steel.

Polished satin finish.

Stainless steel unit thickness: 2mm.

Rounded corners and edges for improved safety.

Smooth surface for easy cleaning.

Suitable for prisons, police stations, etc.

WC pan is completely welded to washbasin, no screws: makes cleaning easier and prevents concealment of objects.

Washbasin equipped with time flow tap: stainless steel tamperproof push-button and anti-blocking system, 7 second time flow, M $\frac{1}{2}$ ".

WC equipped with time flow flush valve, 7 second time flow, M $\frac{3}{4}$ ".

Water inlet: washbasin M $\frac{1}{2}$ ", WC M $\frac{3}{4}$ ".

Recessed horizontal water outlet: \varnothing 100mm.

Supplied with washbasin siphon.



Easy to install: only one water outlet for both washbasin and WC, water inlet and outlet already connected.

Weight: 36kg.

[Formerly ref: 0610030006]

TECHNICAL CHARACTERISTICS

KOMPACT washbasin and floor-standing WC combination - Ref. 160600

Height	1000mm
Length	725mm
Width	735mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS 
Warranty	



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

