KOMPACT washbasin and floor-standing WC combination

Ref. 160700

Polished satin 304 stainless steel, Wall mount, Floor mount WC on LHS



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

DESCRIPTION

KOMPACT washbasin and floor-standing WC combination - Ref. 160700

Combination unit: washbasin and floor-standing WC pan on left sidewith recessed toilet roll holder.

Wall-mounted installation with 3 access panels, 2 on the sidesand 1 on the top with theft prevention TORX security screws.

Bacteriostatic 304 stainless steel.

Polished satin finish

Stainless steel unit thickness: 2mm.

Rounded corners and edges for improved safety.

Smooth surface for easy cleaning.

Suitable for prisons, police stations, etc.

WC pan is completely welded to washbasin, no screws:

makes cleaning easier and prevents concealment of objects.

Washbasin equipped with time flow tap: stainless steel tamperproofpush-

button and anti-blocking system, 7 second time flow, M½".

WC equipped with time flow flush valve, 7 second time flow, M3/1.

Water inlet: washbasin M½", WC M¾".

Recessed horizontal water outlet: Ø 100mm.

Supplied with washbasin siphon.

Easy to install: only one water outlet for both washbasin and WC, water inlet and outlet already connected.

Weight: 36kg.

[Formerly ref: 0610030007]

TECHNICAL CHARACTERISTICS

KOMPACT washbasin and floor-standing WC combination - Ref. 160700

Height	1000mm
Length	725mm
Width	735mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS ①
Warranty	30 g

