DELABIE

KOMPACT washbasin and floor-standing WC combination

Ref. 160800

Satin finish 304 stainless steel, Wall mount, Floor mount central WC

DESCRIPTION

KOMPACT washbasin and floor-standing WC combination - Ref. 160800

Combination unit: washbasin and floor-standing central WC panwith recessed toilet roll holder. Wall-mounted installation with 3 access panels, 2 on the sides and 1 on the top with theft prevention TORX security screws. Bacteriostatic 304 stainless steel. Polished satin finish. Stainless steel unit thickness: 2mm. Rounded corners and edges for improved safety. Smooth surface for easy cleaning. Suitable for prisons, police stations, etc. WC pan is completely welded to washbasin, no screws: makes cleaning easier and prevents concealment of objects. WC pan central to the unit. Washbasin equipped with time flow tap: stainless steel tamperproofpushbutton and anti-blocking system, 7 second time flow, M1/2". WC equipped with time flow flush valve, 7 second time flow, M3/4". Water inlet: washbasin M1/2", WC M3/4". Recessed horizontal water outlet: Ø 100mm. Supplied with washbasin siphon. Easy to install: only one water outlet for both washbasin and WC, water inlet and outlet already connected. Weight: 36kg. [Formerly ref: 0610030008]

TECHNICAL CHARACTERISTICS

KOMPACT washbasin and floor-standing WC combination - Ref. 160800

Height	1000mm
Length	400mm
Width	850mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS
Warranty	30章 WARRANTY



ADVANTAGES



Bacteriostatic 304 stainless steel

Suitable for secure sector

