

KOMPACT TC washbasin and floor-standing WC combination

Ref. 166600

Polished satin 304 stainless steel, cross wall - floor mount WC on RHS



DESCRIPTION

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166600

Combination unit: washbasin and floor-standing WC pan on right sidewith recessed toilet roll holder.
 Service duct installation (through-the-wall).
 Bacteriostatic 304 stainless steel.
 Polished satin finish.
 Stainless steel unit thickness: 2mm.
 Rounded corners and edges for improved safety.
 Smooth surface for easy cleaning.
 Suitable for prisons, police stations, etc.
 WC pan is completely welded to washbasin, no screws:
 makes cleaning easier and prevents concealment of objects.
 Washbasin equipped with time flow tap: stainless steel tamperproofpush-button and anti-blocking system, 7 second time flow, M1/2".
 WC equipped with time flow flush valve, 7 second time flow, M3/4".
 Water inlet: washbasin M1/2", WC M3/4".
 Recessed horizontal water outlet: Ø 100mm
 200mm threaded rod can be cut to size (other lengths available on demand).
 Weight: 30kg.
 [Formerly ref: 0616130006]

TECHNICAL CHARACTERISTICS

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166600

Height	1000mm
Length	615mm
Width	725mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS 
Warranty	



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

