

KOMPACT TC washbasin and floor- standing WC combination

Ref. 166600

Polished satin 304 stainless steel, cross wall - floor mount
WC on RHS



DESCRIPTION

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166600

Combination unit: washbasin and floor-standing WC pan on right sidewith recessed toilet roll holder.
Service duct installation (through-the-wall).
Bacteriostatic 304 stainless steel.
Polished satin finish.
Stainless steel unit thickness: 2mm.
Rounded corners and edges for improved safety.
Smooth surface for easy cleaning.
Suitable for prisons, police stations, etc.
WC pan is completely welded to washbasin, no screws: makes cleaning easier and prevents concealment of objects.
Washbasin equipped with time flow tap: stainless steel tamperproofpush-button and anti-blocking system, 7 second time flow, M1/2".
WC equipped with time flow flush valve, 7 second time flow, M3/4".
Water inlet: washbasin M1/2", WC M3/4".
Recessed horizontal water outlet: Ø 100mm
200mm threaded rod can be cut to size (other lengths available on demand).
Weight: 30kg.
[Formerly ref: 0616130006]

TECHNICAL CHARACTERISTICS

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166600

Height	1000mm
Length	615mm
Width	725mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS 
Warranty	



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

