

KOMPACT TC washbasin and floor-standing WC combination

Ref. 166800

Satin finish 304 stainless steel, cross wall, Floor mount central WC

DESCRIPTION

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166800

Combination unit: washbasin and floor-standing central WC pan with recessed toilet roll holder.

Service duct installation (through-the-wall).

Bacteriostatic 304 stainless steel.

Polished satin finish.

Stainless steel unit thickness: 2mm.

Rounded corners and edges for improved safety.

Smooth surface for easy cleaning.

Suitable for prisons, police stations, etc.

WC pan is completely welded to washbasin, no screws:

makes cleaning easier and prevents concealment of objects.

Washbasin equipped with time flow tap: stainless steel tamperproof push-button and anti-blocking system, 7 second time flow, M1/2".

WC equipped with time flow flush valve, 7 second time flow, M3/4".

Water inlet: washbasin M1/2", WC M3/4".

Recessed horizontal water outlet: Ø 100mm.


200mm threaded rod can be cut to size (other lengths available on demand).

Weight: 30kg.

[Formerly ref: 0616130008]

TECHNICAL CHARACTERISTICS

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166800

Height	1000mm
Length	730mm
Width	400mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS 
Warranty	



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

